



## General Notes

### Overall Dimension

6"Ø x 1-3/4" (D)  
(Excluding Spacers (3) & the  
Steel Plate (2).

### NOTE:

5"Ø Hole required for Glazing  
Panel.

### SPEAK THRU EXPLODED VIEW

1	SECURING SCREWS, 10-32 X 2	3 EACH
2	STAINLESS STEEL PLATE, 6"Ø	1 EACH
3	SPACER, 0.25" I.D.	3 EACH
4	INTERIOR PART, STAINLESS	1 EACH
5	RUBBER GASKET, 5" I.D.	2 EACH
6	EXTERIOR PART, STAINLESS	1 EACH

**QUIKSERV**

11441 BRITTMOORE PARK DR.  
HOUSTON, TX., 77041

TITLE:

**BULLET RESISTANT SPEAK THRU**

Drawing Name

**SPEAK THRU SYSTEM INSTALLATION**

DATE

10/10/2016

DRAWN BY

RBV

SCALE

NTS

SHEET

1 of 2

SIZE

**A**

NOTE: THIS DRAWING EMBODIES A CONFIDENTIAL PROPRIETY DESIGN ORIGINATED AND OWNED BY QUIKSERV CORP., AND IS SUBMITTED UNDER A CONFIDENTIAL RELATIONS ALL PATENT, MANUFACTURING, SALE RIGHTS REGARDING THE SAME ARE RESERVED EXCEPT TO THE EXTENT RIGHTS ARE EXPRESSLY GRANTED TO OTHERS. THE RECIPIENT AGREES BY ACCEPTING HIP. THESE DRAWINGS NOT TO SUPPLY OR DISCLOSE ANY INFORMATION REGARDING THEM TO ANY UNAUTHORIZED PERSON.